

MAHLE

ArcticPRO® Line
Powerful models for A/C service



MAHLE ArcticPRO®

These units are cutting edge when it comes to connectivity and ease of maintenance, with Bluetooth and WiFi, a large touch screen, a status monitoring app, and remote service.

The new generation of service units



EGEA Label

the EGEA label stands for the quality and functionality of professional workshop equipment products. A device that has been developed and designed in accordance with the EGEA specification fulfills all legal requirements and safety standards. The label certifies that MAHLE develops high-quality and effective service units for workshops.

E³ Technology

E³ technology from MAHLE ensures A/C services are ecological, economical, and efficient. Workshops that choose A/C service units from MAHLE also benefit from our Europe-wide service network, technical support, thorough instruction, and comprehensive training.

Always by your side

The formula for A/C service units from MAHLE:

E³ = Ecological × Economical × Efficient

E³ – FILL: Always ready for use, regardless of the vehicle and ambient temperature.
Benefit: Successful filling guaranteed.

E³ – PUMP: The internal cleansing process for the vacuum pump significantly extends oil change intervals. Up to 1,000 operating hours.
Benefit: Significantly reduced maintenance costs.

E³ – CONNECT: Complete recovery of refrigerant from hoses and couplings.
Benefit: No loss of expensive refrigerant.

RE.SOLVE

For MAHLE A/C service units ArcticPRO® Continued support, even remotely.

- RE.SOLVE is MAHLE remote system, allowing owners of the device to profit from immediate technical assistance, even remotely
- Just ask for technical support, and, through a dedicated function, provide the unique code generated by the device and clearly shown on the display
- The authorized technical service operator will then be able to remotely take control of the device and provide suitable assistance



ArcticPRO®

ACX 310 | ACX 410



Advantages at a glance

- Efficient and successful servicing, regardless of the vehicle and ambient temperature
- USB interface for software updates, remote diagnostics
- Extremely compact; ideal mobile solution

Seighs just 65 kg and is extremely compact: our entry-level units

With the ArcticPRO® ACX 310 the ArcticPRO® ACX 410 your workshop can advance to the highest technological level in air conditioning servicing without major investment, while also guaranteeing maximum protection for the environment. Seize this competitive advantage and get ahead of the competition!. These stations incorporates all the technical finesse of our large AC stations range. They are also compact, mobile and stur-

dy. Using ACX 310 and ACX 410 is simple and intuitive, making them a perfect second unit or an ideal mobile solution.

The ArcticPRO® ACX 310 with optional Agricultural database is the perfect assistant to every agricultural and construction machinery engineer. The agricultural machine database and a special multi-stage program optimise the recharging process and fine-tune it to the specific requirements of A/C units that are difficult to access using extended hoses.

| Features | Technical data |
|--|--|
| E ³ – FILL E ³ – PUMP | Dimensions: 544 x 617 x 957 mm |
| High Resolution display | Weight: 65 kg |
| Database for service data (R134a ACX 310 - R1234yf ACX 410) | Reservoir capacity 12 l |
| Easy activation via App | Export of reports as pdf files via USB pen drive |
| Non condensable gas: Automatic check/manual release for ArcticPRO® ACX 310; Automatic for ArcticPRO® ACX 410 | Optional: E ³ – CONNECT; Thermal printer for customer reports; Hybrid Function; N-Leak test Function (with external optional kit); Gas identifier; Agricultural and construction machinery database (ACX 310 only) |
| Oil bottles: 2 (fresh oil, used oil) | |
| Remote assistance (ACX Manager - USB) | |

ArcticPRO®

ACX 320 | ACX 420



Advantages at a glance

- Efficient and successful servicing, regardless of the vehicle and ambient temperature
- USB interface, WiFi, Bluetooth for remote diagnostics, software updates, and ASA connectivity
- Active Oil Protection: hermetically sealed oil containers (optional)
- LED light indicates status anywhere in the workshop

Attractive price/performance ratio; accurate and fully automated work processes: the entry-level ArcticPRO® model

ArcticPRO® ACX 320 (R134a) and ArcticPRO® ACX 420 (R1234yf) look simple, but are extremely performing, providing you with the extraordinary MAHLE technology.

The accurate design is also expressed in the practical use of the ONETOUCH opening system.

The 7" Touchscreen interface guides the less experienced operator and allows the more experienced user to maintain total control of the service.

The WiFi connection ensures constant updating and connecting the station to your printer for the service report at the end.

ArcticPRO® ACX 320, supplied for systems operating with R134a gas, it can easily be converted into R1234yf or the new R513a.

| Features | Technical data |
|---|---|
| E³ – FILL E³ – PUMP | Dimensions: 620 x 720 x 1090 mm |
| 7" high visibility Touchscreen display | Weight 74 kg |
| ONETOUCH liftdoor system | Reservoir capacity: 12 l |
| Database for service data | |
| Automatic purging of non-condensing gas | Optional: E³ – CONNECT; Thermal printer for customer reports; Hybrid Function; N-Leak test Function (with external optional kit); Gas identifier; ASA connectivity via Windows PC Service; Agricultural and construction machinery database (only ACX 320) |
| Oil bottles : 2 (fresh oil, used oil) | |
| Remote assistance (RE.SOLVE - WiFi) | |

ArcticPRO®

ACX 350 | ACX 450



Advantages at a glance

- Efficient and successful servicing, regardless of the vehicle and ambient temperature
- USB interface, WiFi, Bluetooth for remote diagnostics, software updates, and ASA connectivity
- Active Oil Protection: hermetically sealed oil containers
- LED light indicates status anywhere in the workshop
- AC Remote Viewer App: App for remotely viewing the display from your Smartphone with SMS sender service (optional)

Convenient, fast, intuitive; meets the highest requirements in A/C servicing: our Professional units

ArcticPRO® ACX 350 (R134a) and ArcticPRO® ACX 450 (R1234yf) are the perfect compromise for those who want a complete station, equipped with the UV Test function and the ArcticPRO® technologies, at a convenient price level.

The New Oil bottle and the UV Tracer bottle are both equipped with Active Oil Protection system, the special lid that prevents any contamination from moisture found in the air.

ArcticPRO® ACX 350 and ArcticPRO® ACX 450 can connect to MAHLE diagnostic devices to enhance the management of particular maintenance functions.

Simple to use, thanks to the intuitive graphics of its touch interface, and due to its capacitive display that allows to operate even when wearing protective gloves. All updates, software and databases, are self-installed via to the integrated WiFi connection. ArcticPRO® ACX 350 can be easily converted for managing the R1234yf, or if necessary, also the new R513a, thanks to convenient conversion kits and special software.

| Features | Technical data |
|--|---|
| E³ – FILL E³ – PUMP E³ – CONNECT | Dimensions: 620 x 720 x 1090 mm |
| 7" high visibility Touchscreen display | Weight: 74 kg |
| ONETOUCH liftdoor system | Reservoir capacity: 20 l |
| Database for service data | |
| Automatic purging of non-condensing gas | Optional: Thermal printer for customer reports; Integrated N-Leak test Function (can be activated via GoLive); Gas identifier; ASA connectivity via Windows PC Service; VCI A/C diagnostics (SW & HW); Agricultural and construction machinery database (only ACX 350) |
| Oil bottles : 3 + 1 - fresh oil (PAG), used oil, UV additive + POE | |
| Remote assistance (RE.SOLVE - WIFI) | |

ArcticPRO®

ACX 380 | ACX 480



Advantages at a glance

- Efficient and successful servicing, regardless of the vehicle and ambient temperature
- USB interface, WiFi, Bluetooth for remote diagnostics, software updates, and ASA connectivity
- Active Oil Protection: hermetically sealed oil containers
- LED light indicates status anywhere in the workshop
- AC Remote Viewer App: App for remotely viewing the display from your Smartphone with SMS sender service

Maximum safety and high-end precision/First-class service at the touch of a button: our premium units

ArcticPRO® ACX 380 (R134a) and ArcticPRO® ACX 480 (R1234yf) are the Top Level A/C stations in the series. You could not wish for more. From the ergonomic design of the hardware to the software developed by carefully analysing your daily activities in the workshop.

The integrated WiFi connection is the constant element of the entire line, which

allows to fully exploit all the innovative features. The integration with MAHLE diagnostic tools also enhance its field of action. The integration of our special APPs is innovative and useful, as it is able to control, service and remote the display: this ensures convenience and interactivity, thus making the AC recharge service a customer retention tool. Anche

ArcticPRO® ACX 380, for R134a systems, is easily convertible into R1234yf, or if necessary, also in the new R513a.

| Features | Technical data |
|--|---|
| E³ – FILL E³ – PUMP E³ – CONNECT | Dimensions: 620 x 720 x 1090 mm |
| 7" high visibility Touchscreen display | Weight: 74 kg |
| ONETOUCH liftdoor system | Reservoir capacity 20 l |
| Database for service data | |
| Automatic purging of non-condensing gas | Optional: Integrated N-Leak test Function (can be activated via GoLive); Gas identifier; ASA connectivity via Windows PC Service; VCI A/C diagnostics (SW & HW); Agricultural and construction machinery database (only ACX 380) |
| Oil bottles : 4 - fresh oil (PAG & POE), used oil, UV additive | |
| Remote assistance (RE.SOLVE - WiFi) | |

ArcticPRO® ACX 255



Advantages at a glance

- Efficient and successful servicing, regardless of the vehicle and ambient temperature
- USB interface for software updates, remote diagnostics
- ACX RFID gas identifier included (external)
- VDA approved (German Association of the Automotive Industry)
- Active Oil Protection: hermetically sealed oil containers (optional)

Best-in-class with intelligent add-on function: our premium unit

ArcticPRO® ACX 255, approved by VDA, German Association of the Automotive Industry, complies with every OEM requirements.

An ample tank and the vacuum pump ensure a generous, capacity and excellent vacuum

The patented Injection charging system guarantees a degree of accuracy far in excess of the standard requirements.

ArcticPRO® ACX 255 is equipped with an integrated gas identifier, located outside of the unit for an easier routine maintenance.

ArcticPRO® ACX 255 comes with an emergency stop button, and is also equipped with a built-in thermal printer for customer reports.

| Features | Technical data |
|--|-----------------------------------|
| Incl. ACX RFID refrigerant analysis unit and TÜV certification | Dimensions: : 700 x 700 x 1100 mm |
| VDA approved | Weight: 65 kg |
| Color touch screen | Reservoir capacity: 20 l |
| Database for service data | |

Accessories



ROU – Recovery Only Unit

Removes unknown and contaminated refrigerants from vehicle air conditioning systems simply and safely.

Ecological: Professional and safe disposal protects people and the environment; **Economical:** The ROU is immediately ready to use together with an A/C service unit. No other materials and supplies are required; **Efficient:** Our patented internal cycle guarantees a fast service with a 95% recovery rate within 30 minutes.

ACX universal flushing unit for refrigerants R134a and R1234yf

Flushing tank with support for flexible usage — entirely independent of the A/C service unit location and model.

Ergonomically positioned: Control sight glass to check flushing process and refrigerant purity; Flexible application: HP hose connector adapter set for various A/C service units; Flushing adapter set (3/8" and 1/4") allows connection to all standard flushing adapters for air conditioning systems or to a system's individual components; Coupling adapter set for refrigerants R134a and R1234yf to connect the LP coupling to the flushing unit; Optional: Protective storage cover.

ACX RFID

External analysis unit for the MAHLE ACX A/C service unit for refrigerant R1234yf and R1234yf

Offers maximum protection to A/C service units; Safe analysis via LP coupling; Plug and play consente Plug and play allows immediate integration with the unit.; Simple, automatic operation and instant measurement result; Fully automated control via integrated software process.

IDX 500

Internal analysis unit for the MAHLE ACX A/C service unit for refrigerant R134a and R1234yf.

Quicker than previous model; Can detect mixtures of R134a - R1234yf at any concentration.; Offers maximum protection to A/C service units; Safe analysis via LP coupling; Plug and play allows immediate integration with the unit; Simple, automatic operation and instant measurement result; Fully automated control via integrated software process.



| A/C service units | ACX 310 | ACX 320 | ACX 350 |
|--|-------------------------------------|---------------------------|---|
| Refrigerant | R134a | Convertible | Convertible |
| Convertible to refrigerant R1234yf | | + | + |
| Convertible to refrigerant R513a | | + | + |
| Vacuum pump | HPV 0.02 mbar | HPV 0.02 mbar | |
| Refrigerant tank | 12 L | 12 L | 20 L |
| Compressor | 8 cc | 8 cc | 14 cc |
| Filter drier capacity | 75 kg | 75 kg | 150 kg |
| Recovery rate | >95% | >95% | >95% |
| Pressure sensors | LP | LP | Tank, LP, HP |
| Oil bottles | 2 (fresh oil, used oil) | 2 (fresh oil, used oil) | 3 + 1 fresh oil (PAG), used oil, UV additive + POE (in scope of delivery) |
| Containers Active Oil Protection (hermetically sealed oil bottles) | | ■ | + |
| Oil scales | | 1 | 2 (fresh oil, used oil) |
| Operating temperature | 10°C to 50°C | 10°C to 50°C | 10°C to 50°C |
| Power supply | 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W |
| Length of service hoses | 3 m | 4,5 m | 4.5 m |
| Optional: Extension of service hose to | 6 m | 7,5 m | 7.5 m |
| Display | B&W 35x200 4 lines/30 characters | 7" TFT color touch screen | 7" TFT color touch screen |
| Keypad | 4 direction keys, Enter, Esc. | Touch screen | Touch screen |
| Menu languages | 25 | 25 | 25 |
| Warranty | 24 months | 24 months | 24 months |
| Certifications | CE, PED | CE, PED | CE, PED |
| Noncondensable gases through air purge system | Automatic check/manual release | Automatic | Fully automatic |
| Automatic recovery and injection of refrigerant | + | + | + |
| Automatic recovery of compressor oil | + | + | + |
| Automatic injection of UV dye | | | + |
| Manual operating mode | + | + | + |
| Automatic hose compensation | + | + | + |
| E ³ – fill (always ready for use, regardless of the vehicle and ambient temperature) | + | + | + |
| E ³ – pump (vacuum pump oil change after 1,000 h.) | + | + | + |
| E ³ – connect (complete recovery of refrigerant from hoses and service couplings) | ■ | ■ | + |
| A/C performance test (for dynamic performance testing of the A/C system in only 10 minutes with a customer report) | + | + | + |
| Tank pressure reading | + | + | + |
| Refrigerant analyzer | | ■ | ■ |
| Compatibility with hybrid vehicles | ■ | ■ | + |
| Electronic car database | + | + | + |
| Agricultural and construction machinery database | ■ | ■ | ■ |
| Test di tenuta azoto, kit opzionale richiesto | + | + | |
| Nitrogen leak test—integrated connection, no optional connector required, the function can be activated via GoLive | | | ■ |
| Nitrogen leak test, optional kit required | + | + | |
| Forming gas leak test—integrated connection, optional connector required | | | ■ |
| Status indicator lights | | + | + |
| Thermal Printer | ■ | ■ | ■ |
| Network printout via Windows PC service | | + | + |
| Usb interface | + | + | + |
| WiFi | | + | + |
| Bluetooth | | + | + |
| ASA connectivity via Windows PC service | | ■ | ■ |
| VCI A/C Diagnostics (SW & HW) | | | ■ |
| AC Remote Viewer app with SMS service | | | ■ |
| Remote assistance | USB | WiFi | WiFi |

| ACX 380 | ACX 410 | ACX 420 | ACX 450 | ACX 480 | ACX 255 |
|---|-------------------------------------|---------------------------|---|---|---|
| Convertible | R1234yf | R1234yf | R1234yf | R1234yf | R1234yf |
| + | | | | | |
| + | | | | | |
| | HPV 0.02 mbar | HPV 0.02 mbar | | | |
| 20 L | 12 L | 12 L | 20 L | 20 L | 20 L |
| 14 cc | 8 cc | 14 cc | 14 cc | 14 cc | 14 cc |
| 150 kg | 75 kg | 100 kg | 150 kg | 150 kg | 150 kg |
| >95% | >95% | >95% | >95% | >95% | >95% |
| Tank, LP, HP | LP | LP | Tank, LP, HP | Tank, LP, HP | Tank, LP, HP |
| 4 fresh oil, (PAG & POE), used oil, UV additive | 2 (fresh oil, used oil) | 2 (fresh oil, used oil) | 3 + 1 fresh oil (PAG), used oil, UV additive + POE (in scope of delivery) | 4 fresh oil, (PAG & POE), used oil, UV additive | 4 fresh oil, (PAG & POE), used oil, UV additive |
| + | | ■ | + | + | + |
| 4 | | 1 | 2 (fresh oil, used oil) | 4 | 1 |
| 10°C to 50°C | 10°C to 50°C | 10°C to 50°C | 10°C to 50°C | 10°C to 50°C | 10°C to 50°C |
| 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W | 230 V, 50 Hz, 800 W |
| 4.5 m | 3 m | 4.5 m | 4.5 m | 4.5 m | 3 m |
| 7.5 m | 6 m | 7.5 m | 7.5 m | 7.5 m | |
| 7" TFT color touch screen | B&W 35x200 4 lines/30 characters | 7" TFT color touch screen | 7" TFT color touch screen | 7" TFT color touch screen | 7" TFT color touch screen |
| Touch screen | 4 tasti direzionali, Enter, Esc. | Touch screen | Touch screen | Touch screen | Touch screen |
| 25 | 25 | 25 | 25 | 25 | 25 |
| 24 months | 24 months | 24 months | 24 months | 24 months | 24 months |
| CE, PED | CE, PED | CE, PED | CE, PED | CE, PED | CE, PED, TÜV, VDA approved |
| Fully automatic | Automatic check/manual release | Automatic | Fully automatic | Fully automatic | Fully automatic |
| + | + | + | + | + | + |
| + | + | + | + | + | + |
| + | | | + | + | + |
| + | + | + | + | + | + |
| + | + | + | + | + | + |
| + | + | + | + | + | + |
| + | + | + | + | + | + |
| + | + | ■ | + | + | + |
| + | + | + | + | + | |
| + | + | + | + | + | + |
| ■ | ■ | ■ | ■ | ■ | + |
| + | ■ | ■ | + | + | + |
| + | ■ | + | + | + | ■ |
| ■ | | | | | |
| + | + | + | | + | |
| + | + | + | | | |
| + | | | ■ | + | |
| + | | + | ■ | + | |
| + | ■ | ■ | ■ | + | + |
| + | | + | + | + | |
| + | + | + | + | + | + |
| + | | + | + | + | |
| + | | + | + | + | |
| + | | + | + | + | |
| + | | + | + | + | |
| ■ | | ■ | ■ | ■ | |
| ■ | | | ■ | ■ | |
| + | | | ■ | + | |
| WiFi | USB | WiFi | WiFi | WiFi | USB |

MAHLE Aftermarket Italy S.P.A.
Via Rudolf Diesel 10/a
43122 Parma
Italia
Tel. +39 0521 9544-11
Fax +39 0521 9544-90
info.aftermarket@mahle.com

MAHLE Aftermarket Deutschland GmbH
Dürrheimer Straße 49a
D-78166 Donaueschingen
Germania
Tel. +49 771 89653-24200
Fax +49 771 89653-24290
mss.sales.de@mahle.com

MAHLE Aftermarket S.L.U.
C/Mario Vargas Llosa 13
Pol ind Casablanca
28850 Torrejón de Ardoz, Madrid
Spagna
Tel. + 34 91 888 6799
Fax + 34 91 888 6311
administracion.iberica@mahle.com

www.mahle-aftermarket.com
www.mpulse.mahle.com